

RIPACK 2100
RIPACK QUALITY AT LOW PRICE



The Ripack 2100 is the ideal tool to get started in the shrink world, or for occasional shrink needs.

With a fixed power of 40 kW, the Ripack 2100 will be your best ally for shrinking films up to 150 microns.

Reliability and safety being the key words for Ripack, this shrink gun is equipped with the patented «cold nozzle» technology, as well as a Securipack pressure regulator. This ensures the highest level of safety and constantly monitors the gas cylinder pressure and the pressure of the device.

With its patented no tool piezo changeover system in the handle, save time and efficiency.

TECHNICAL SPECIFICATIONS

Power	40 kW
Pressure	2,5 bars
Length/Height	14,17"/10,36" - 360/262 mm
Package dimensions	460x330x140 mm 18,11" x 13" x 5,51"
Weight	2,11 lb / 955 g
Package weight	10,69 lb / 4850 g
Noise level	< 85 dbA
Energy source	Propane gas or natural gas upon request



Each gun is delivered in a carrying case with: 1 SECURIPACK FIXED gas regulator, 1 8-meter hose with crimped connection, 1 key for tightening/untightening the connections, 1 user manual with CE certificate.

EQUIPMENT SOLD SEPARATELY AND IN KIT



936 GAS BOTTLE TROLLEY



GAS HOSE REEL



MULTICOVER 960

Please refer to the regulations applicable in the country of use concerning the conformity and use of the products and accessories offered in our Ripack® range. All information and photos in this brochure refer to product specifications updated at the time of publication according to the date mentioned on this page. RIPACK® reserves the right to change the colors, materials, features and specifications of its products at any time. Some products may be shown with accessories and/or features not available in some countries. All rights reserved. Reproduction in any form and by any means is prohibited without previous authorization from RIPACK®.

* guarantee for labor and parts; www.ripack.com

