

YOUR PROTECTION

BY EXCELLENCE

MULTICOVER 960

THE PEARL OF WELDING MACHINES











Multicover 960 enables cost savings by easy self-doing of pallet covers of different sizes according to need from heat shrinkable polyethylene film rolls. Avoid the costly stock of various sizes.

Using Multicover 960 is easy and fast

- Begin the passage of 3 to 5 cm of the film between the sealing bars.
- Lower one of the levers to make a perfect welding of a 3 mm width seal using the adjustment of temporization according to the thickness of film.
- Set the meter to zero. Open the sealing bars then unroll the film at the exact desired length.
- Close the sealing bars to make a welding which will be next cover. No need to wait for the end of this sealing before cutting and using the cover.
- Cut the film by moving the sliding carriage knife and separate the cover by pulling it slightly.

The non-return, eccentric rollers maintain film in position.

The dispenser Multicover 935 allows using up to 5 reels simultaneously. With the casters the set becomes completely mobile.

TECHNICAL SPECIFICATIONS

Item Code
Sealing method
Power supply
Cutting process
Maximum sealing capacity
Maximum admissible roll

Length/Width/Height

Weight Package dimensions

Package weight

N°349025

Adjustable electrical impulse 230V (50/60 Hz) - 24V . 0.5kVA Sliding knife

4 x 200 μ / width 1440 mm Ø 500mm - width 1500mm -220,46 lb - 100kg

1970 x 580 x 1430 mm 77,56" x 22,83" x 56,3"

209,44 lb - 95 Kg 2150 x 750 x 1450 mm

84,65" x 29,53" x 57,09" 352,74 lb - 160 Kg

EQUIPMENT SOLD SEPARATELY



GUSSETED HEAT SHRINK TUBING (AVAILABLE FROM 4 TO 15 M WIDE)



STANDARD PALLET COVER (80X120 AND 100X120)



