

TURBOPACK
TOTAL PROTECTION, PERFECT PACKING



The Turbopack is a mobile heating column, loaded on an easily movable trolley. It gives the operator the possibility to heat-shrink his load anywhere in the shipping area, very useful to avoid the movement of unstable loads.

The benefit of the Turbopack solution is that it does not require any other investment, no fixed power supply or conveyors. No limitation on the length or width of the load (unlike frames or ovens) and up to 3.20 m height. A real argument for very long pallets or the shrinkwrapping of pallets of different sizes.

Its unique design allows for a surge of hot air flow for unmatched efficiency, even on thick films. 45 seconds are enough to heat-shrink a pallet (Euro type) up to 3.2 meters. You can shrink-wrap up to 290 pallets with 3 gas cylinders.

Adapting to your load is very simple, a series of shutoff valves allow you to consume the right amount of gas and the heat reflector (visor) plate (optional) can be adjusted with a simple gesture with the help of a balancer. No need for complex programming, tedious handling or long and costly training.

Finally, safety being the major asset of our innovations, the Turbopack incorporates a double handle system that cuts off the gas supply in the event that one of them is released, safety valves on each cylinder detecting pipe breaks and guiding wheels avoiding contact with the load.



800 mm



1200 mm



1600 mm



2000 mm



2400 mm



3200 mm

TECHNICAL SPECIFICATIONS

Height (mm)	800	1200	1600	2000	2400	3200
Item code	N°350238	N°350237	N°350236	N°350235	N°350234	N°350239
Power developed	75 kW	110 kW	143 kW	177 kW	210 kW	280 kW
Consumption	5,48 kg/h	8 kg/h	10,35 kg/h	12,79 kg/h	15 kg/h	20 kg/h
Working pressure	1,5 to 2,5 bars					
Minimum space around the pallet	1400 mm 55,12"					
Net weight	94 kg 207 lb	104 kg 229 lb	112 kg 247 lb	122 kg 269 lb	131 kg 289 lb	150 kg 331 lb
Visor option N°235319	No	No	Yes	Yes	Yes	No



Please refer to the regulations applicable in the country of use concerning the conformity and use of the products and accessories offered in our Ripack® range. All information and photos in this brochure refer to product specifications updated at the time of publication according to the date mentioned on this page. RIPACK® reserves the right to change the colors, materials, features and specifications of its products at any time. Some products may be shown with accessories and/or features not available in some countries. All rights reserved. Reproduction in any form and by any means is prohibited without previous authorization from RIPACK®.

* guarantee for labor and parts; www.ripack.com

www.ripack.com

